

**FDV DOCUMENTATION**

Rod Mini C 1750lm 927 20° 15W WH 3-circuit

Art.no: 102530-20-3

*Lighting Solutions*

Rod Mini C 1750lm 927 20° 15W WH 3-circuit



SPECIFICATIONS	
Type of Dimming (system)	None
IK	IK02
Operating temperature (°C)	45
Color Code	927
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
Forward Voltage LED (max tp=25) (V)	38.0
Forward Voltage LED (min tp=65) (V)	33.0
Protection Class (driver)	2
Dimming (driver)	None
Constant current or voltage (CC or CV)	CC



FDV DOCUMENTATION
Rod Mini C 1750lm 927 20° 15W WH 3-circuit
Art.no: 102530-20-3



SPECIFICATIONS	
CC (driver) [mA]	1050
CC (forward voltage driver) (V)	42.0
Inrush current time (µs)	70.0
Inrush current I _{max} (A)	2.025
Width (product) (mm)	75.0
Height (product) (mm)	85.0
Weight (product) (kg)	0.5333333333333333
Diameter (product) (mm)	75.0
Color	White
RAL Code	RAL9010
Mounting	Track, Ceiling
Connection (system)	Track 3-Circuit