



FAMILY PRODUCT SHEET

Rod Mini C

Art.no: Rod-Mini-C



Lighting Solutions



Rod Mini C



Rod Mini C is a compact and elegant spotlight developed for 3-phase track systems, combining high efficiency with exceptional flexibility. It delivers impressive lumens per watt, placing it among the top performers in terms of efficiency and energy savings. With its extensive adjustment capabilities, Rod Mini C is ideal for retail environments and other applications where precise lighting is essential. It gives lighting designers full control over beam direction and visual expression, making it easy to create both atmospheric and functional lighting installations. The spotlight is available in three different colours and with two reflector options, allowing it to be adapted to various interior styles and project requirements. For enhanced visual comfort and reduced glare, a honeycomb louvre is available as an optional accessory.

VARIANTS

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Connection	Color
102530-36-1	15W	1750 lm	2700K	36	Clear	90	None	Skinne 3-fase	Grey
102530-36-2	15W	1750 lm	2700K	36	Clear	90	None	Skinne 3-fase	Black
102530-36-3	15W	1750 lm	2700K	36	Clear	90	None	Skinne 3-fase	White
102531-20-1	15W	1800 lm	3000K	20	Clear	90	None	Skinne 3-fase	Grey
102531-20-2	15W	1800 lm	3000K	20	Clear	90	None	Skinne 3-fase	Black
102531-20-3	15W	1800 lm	3000K	20	Clear	90	None	Skinne 3-fase	White
102531-36-1	15W	1800 lm	3000K	36	Clear	90	None	Skinne 3-fase	Grey

**FAMILY PRODUCT SHEET**

Rod Mini C

Art.no: Rod-Mini-C

*Lighting Solutions*

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Connection	Color
102531-36-2	15W	1800 lm	3000K	36°	Clear	90	None	Skinne 3-fase	Black
102531-36-3	15W	1800 lm	3000K	36°	Clear	90	None	Skinne 3-fase	White
102533-36-3	15W	1800 lm	Arctic WhiteK	36°	Clear	90	None	Skinne 3-fase	White
102530-60-2	15W	1750 lm	2700K	60°	Clear	90	None	Skinne 3-fase	Black
102530-20-2	15W	1750 lm	2700K	20°	Clear	90	None	Skinne 3-fase	Black
102530-20-3	15W	1750 lm	2700K	20°	Clear	90	None	Skinne 3-fase	White
102530-60-3	15W	1750 lm	2700K	60°	Clear	90	None	Skinne 3-fase	White
102532-60-2	15W	1750 lm	Arctic WhiteK	60°	Clear	90	None	Skinne 3-fase	Black
102532-60-3	15W	1750 lm	Arctic WhiteK	60°	Clear	90	None	Skinne 3-fase	White
102532-36-2	15W	1750 lm	Arctic WhiteK	36°	Clear	90	None	Skinne 3-fase	Black
102532-20-2	15W	1750 lm	Arctic WhiteK	20°	Clear	90	None	Skinne 3-fase	Black
102532-20-3	15W	1800 lm	Arctic WhiteK	20°	Clear	90	None	Skinne 3-fase	White