




CBU 1-ch 0-10V/Dali Casambi



The AIMOTION controller controls individual luminaires in the Bluetooth Low Energy Mesh network without the use of gateways, routers, repeaters or extra cabling. Configuration and selection of the appropriate profile for the different operating modes (4xDIM, TW, RGB, RGBW, etc.) is carried out wirelessly via the Casambi App.

ELECTRICAL DATA	
Dimming (system)	DALI, 0-10V, 1-10V
Voltage (system) [V]	230V 50Hz
Frequency (Hz)	50Hz
Max Power (A)	0.6

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-20 - 50
Last Level	Yes



TECHNICAL DATA

Soft Start	Yes
------------	-----

DIMENSIONS

Length (product) (mm)	56.5
Width (product) (mm)	22.3
Height (product) (mm)	35.8
Weight (product) (kg)	0.05
Cable Dimension	0,75-1,5 mm2

MATERIALS AND SURFACES

Color	White
Housing	II

INSTALLATION AND CONNECTION

Mounting Dimmer	Electrical box
-----------------	----------------

ENERGY AND CERTIFICATIONS

CE mark	Yes
Dimmer Standard	EN60669
Energy Efficiency Class	A++ - A