

**FDV DOCUMENTATION**

Rod Midi C 4100lm 935 20° 23W WH 3-circuit

Art.no: 102312-20-3



Rod Midi C 4100lm 935 20° 23W WH 3-circuit



PRODUCT DESCRIPTION

Rod Midi C is a powerful and flexible spotlight developed for modern retail, showroom, and project lighting applications. Featuring a sleek cylindrical design and high light output, the luminaire combines aesthetics and performance, making it suitable for both accent and general lighting. Delivering up to 4100 lumens with excellent colour rendering (CRI90), Rod Midi C ensures natural presentation of products, materials, and interior details. Available with multiple beam angles and colour temperatures, the spotlight can easily be adapted to different environments and lighting requirements. It is offered in white, black, or grey finishes and is designed for easy installation in 3-circuit track systems. Selected versions are also available with DALI control for advanced lighting management solutions. Rod Midi C is an ideal choice for retail stores, exhibition areas, galleries, hotels, and restaurants where high lighting quality, flexibility, and an exclusive appearance are essential.

FUNCTIONALITY DESCRIPTION

Rod Midi C is a compact and elegant spotlight designed for 3-circuit track systems, offering high efficiency and exceptional flexibility. It delivers impressive lumens per watt, placing it among the top performers in terms of light output and energy efficiency. With extensive adjustment possibilities, Rod Midi C is ideal for retail environments and applications where precise lighting is critical. It provides lighting designers with full control over direction and visual expression, making it easy to create both functional and atmospheric installations. The spotlight is available in three different colours and with four reflector options, allowing seamless adaptation to a wide range of interiors and lighting requirements.

MAINTENANCE

Clean with a dry cloth

SPECIFICATIONS	
Type of Dimming (system)	None
IK	IK02
Operating temperature (°C)	45
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
Forward Voltage LED (max tp=25) (V)	38.0

**FDV DOCUMENTATION**

Rod Midi C 4100lm 935 20° 23W WH 3-circuit

Art.no: 102312-20-3

*Lighting Solutions*

SPECIFICATIONS	
Forward Voltage LED (min tp=65) (V)	33.0
Protection Class (driver)	2
Dimming (driver)	None
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	1000
CC (forward voltage driver) (V)	42.0
Inrush current time (μ s)	70.0
Inrush current I _{max} (A)	2.025
Height (product) (mm)	115.0
Weight (product) (kg)	0.66
Diameter (product) (mm)	97.0
Color	White
RAL Code	RAL9010
Mounting	Track, Ceiling
Connection (system)	Track 3-Circuit