



PRODUCT DATA SHEET


NSW M Pro Dual AiColor+People Counting 30W 24° Recessed WH
Art.no: 103240-24-3



Lighting Solutions



NSW M Pro Dual AiColor+People Counting 30W 24° Recessed WH



ELECTRICAL DATA

Protection Class (system)	2
Dimming (system)	AIoT or APP (Bluetooth connected)
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA

IK (system)	IK06
IP (system)	IP20
Operating temperature (°C)	-10 - 30

PHOTOMETRIC DATA

Efficacy (system) (lm/W)	73
--------------------------	----

**PRODUCT DATA SHEET**

NSW M Pro Dual AlColor+People Counting 30W 24° Recessed WH
Art.no: 103240-24-3

*Lighting Solutions*

PHOTOMETRIC DATA	
CRI / Ra ($\geq$)	90
CCT (Color Temperature) (K)	2700-6500
Color Code	RGBW
Lightsource Type	LED (built in)
Lens (Diffuser)	Lens
Lifetime (h) IEC 62717	L80B10: 100 000
MacAdam (SDCM)	3
UGR ($\leq$)	7
Manufacturer (light source)	Ledteen
Forward Voltage LED (max $t_p=25$) (V)	36.0
Driftspenning LED (min $t_p=65$) (V)	36.0

DRIVER	
Manufacturer (driver)	Kinglumi
Flicker-free	Yes

CONTROL SYSTEM	
Mesh	Yes
System	NWC

DIMENSIONS	
Width (product) (mm)	118.0
Height (product) (mm)	175.0
Weight (product) (kg)	1.125
Diameter (product) (mm)	118.0

MATERIALS AND SURFACES	
Color	White
Corrosion Class	C1

INSTALLATION AND CONNECTION	
Areas of use	Shop
Mounting	Recessed
Connection (system)	QuickConnect

**PRODUCT DATA SHEET**

NSW M Pro Dual AlColor+People Counting 30W 24° Recessed WH
Art.no: 103240-24-3



Lighting Solutions

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	F
CE mark	Yes