

**PRODUCT DATA SHEET**

NLL 55 Module Indirect/Uplight 1500lm 940/930 10W

Art.no: 103451-1200-04

*Lighting Solutions*

NLL 55 Module Indirect/Uplight 1500lm 940/930 10W



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	DALI2
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK06
IP (system)	IP20
IP Front/Back (system)	IP20/20
Outdoor	No
Operating temperature (°C)	-20 - 40

PHOTOMETRIC DATA	
CRI / Ra (>=)	90

**PRODUCT DATA SHEET**

NLL 55 Module Indirect/Uplight 1500lm 940/930 10W

Art.no: 103451-1200-04

*Lighting Solutions*

PHOTOMETRIC DATA	
CCT (Color Temperature) (K)	3000/4000
Preset CCT if switch(Color Temperature) (K)	3000
Color Code	930/940
Lightsource Type	LED (replaceable)
Socket / Cap-Base	N/A
Lens (Diffuser)	Frosted
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
Manufacturer (light source)	Shenzhen leadopto Technology Co.Ltd

DRIVER	
Flicker-free	Yes

DIMENSIONS	
Length (product) (mm)	870.0
Width (product) (mm)	24.5
Height (product) (mm)	14.0
Weight (product) (kg)	0.1

MATERIALS AND SURFACES	
Surface treatment	Powdercoated
Housing Material	Aluminium
Diffuser Material	Polycarbonate

INSTALLATION AND CONNECTION	
Areas of use	Office
Mounting	Recessed, Surface, Track, Wall
Connection (system)	QuickConnect

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	D
CE mark	Yes