

**PRODUCT DATA SHEET**

NLL 55 L-Module 3700lm 940/930 Microprismatic 32W Dali

Art.no: 103451-650-02-ddd



NLL 55 L-Module 3700lm 940/930 Microprismatic 32W Dali



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	DALI2
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK06
IP (system)	IP20
IP Front/Back (system)	IP20/20
Outdoor	No
Operating temperature (°C)	-20 - 40

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	115
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	3000/4000
Preset CCT if switch(Color Temperature) (K)	3000
Color Code	930/940
Lightsource Type	LED (replaceable)
Socket / Cap-Base	N/A
Lens (Diffuser)	Prismatic
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
UGR (<=)	23
Manufacturer (light source)	Shenzhen leadopto Technology Co.Ltd

**PRODUCT DATA SHEET**

NLL 55 L-Module 3700lm 940/930 Microprismatic 32W Dali

Art.no: 103451-650-02-ddd

*Lighting Solutions***PHOTOMETRIC DATA**

Forward Current LED (min-max) (mA)	200 - 350
------------------------------------	-----------

DRIVER

Manufacturer (driver)	Boke
Flicker-free	Yes

DIMENSIONS

Length (product) (mm)	598.0
Width (product) (mm)	48.0
Height (product) (mm)	42.0
Weight (product) (kg)	0.88

MATERIALS AND SURFACES

Surface treatment	Powdercoated
Housing Material	Steel
Diffuser Material	Polycarbonate

INSTALLATION AND CONNECTION

Areas of use	Office
Mounting	Recessed, Surface, Track, Wall
Connection (system)	QuickConnect

ENERGY AND CERTIFICATIONS

Energy Class EPREL	C
CE mark	Yes