

**FDV DOCUMENTATION**

Trunk NWC 830 Narrow 60° 50W 1500mm 3000K WH PIR

Art.no: CFL-P-NW-1550-30NR-08-3



Trunk NWC 830 Narrow 60° 50W 1500mm 3000K WH PIR

**MAINTENANCE**

Clean with a dry cloth

SPECIFICATIONS	
Type of Dimming (system)	Norlux Wireless Connect
IK	IK04
Operating temperature (°C)	40
Through-wiring (mm ²)	8x2,5
Color Code	830
Lightsource Type	LED (built in)
Lifetime (h)	50 000
MacAdam (SDCM)	3
Forward Voltage LED (max tp=25) (V)	40.0
Forward Voltage LED (min tp=65) (V)	12.0
Length (product) (mm)	1500.0
Width (product) (mm)	70.0

**FDV DOCUMENTATION**

Trunk NWC 830 Narrow 60° 50W 1500mm 3000K WH PIR

Art.no: CFL-P-NW-1550-30NR-08-3

*Lighting Solutions*

SPECIFICATIONS	
Height (product) (mm)	40.0
Weight (product) (kg)	1.7
Color	White
RAL Code	RAL9016
Mounting	Suspended
Connection (system)	Trunk 8-wires
Emergency light (h)	No Emergency light
Emergency light testing	N/A