

**PRODUCT DATA SHEET**

Trunk NWC 830 Narrow 60° 50W 1500mm 3000K WH PIR

Art.no: CFL-P-NW-1550-30NR-08-3



Trunk NWC 830 Narrow 60° 50W 1500mm 3000K WH PIR



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	Norlux Wireless Connect
Voltage (system) [V]	230V 50Hz / 176-275VDC
Emergency light (h)	No Emergency light
Emergency light testing	N/A

TECHNICAL DATA	
IK (system)	IK04
IP (system)	IP40
IP Front/Back (system)	IP40/20
Outdoor	No
Operating temperature (°C)	-25 - 40
Through-wiring (mm ²)	8x2,5

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	180
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Lightsource Type	LED (built in)
Lens (Diffuser)	Lens
Lifetime (h)	50 000
MacAdam (SDCM)	3
UGR (<=)	28
Manufacturer (light source)	Bridgelux
Forward Current LED (min-max) (mA)	850 - 1200

**PRODUCT DATA SHEET**

Trunk NWC 830 Narrow 60° 50W 1500mm 3000K WH PIR

Art.no: CFL-P-NW-1550-30NR-08-3

*Lighting Solutions***PHOTOMETRIC DATA**

Forward Voltage LED (max tp=25) (V)	40.0
Driftspenning LED (min tp=65) (V)	12.0

DRIVER

Manufacturer (driver)	Boke
Flicker-free	Yes

CONTROL SYSTEM

Norlux Wireless Connect	Implemented
System	NWC

DIMENSIONS

Length (product) (mm)	1500.0
Width (product) (mm)	70.0
Height (product) (mm)	40.0
Weight (product) (kg)	1.7

MATERIALS AND SURFACES

Color	White
RAL Code	RAL9016
Corrosion Class	C3
Housing Material	Steel
Diffuser Material	PMMA

INSTALLATION AND CONNECTION

Areas of use	Shop
Mounting	Suspended
Connection (system)	Trunk 8-wires

ENERGY AND CERTIFICATIONS

Energy Class EPREL	C
CE mark	Yes