




PRODUCT DATA SHEET
Driver On/Off 350mA max 15W 23-42V 18i3 Male/ EPN0034
Art.no: 0300-39



Driver On/Off 350mA max 15W 23-42V 18i3 Male/ EPN0034



ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Connection 1	18i3 male
Connection 2	EPN0034 female

DRIVER	
Manufacturer (driver)	Osram
Protection Class (driver)	2
Flicker metric (Pst LM) <	1.0

**PRODUCT DATA SHEET**

Driver On/Off 350mA max 15W 23-42V 18i3 Male/ EPN0034

Art.no: 0300-39

*Lighting Solutions*

DRIVER	
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	60
Dimming (driver)	None
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	250 - 500
Current setting (driver)	DIP-switch
CC (forward voltage driver) (V)	23.0 - 42.0
Current Ripple (%)	5.0
Max load pr circuit - B10	60
Max load pr circuit - B16	38
Max load pr circuit - C10	57
Max load pr circuit - C16	91
Max load pr circuit - C25	142
Inrush current I _{max} (A)	4.0

DIMENSIONS	
Length (product) (mm)	97.0
Width (product) (mm)	43.0
Height (product) (mm)	29.5
Weight (product) (kg)	0.075