

**PRODUCT DATA SHEET**

Riva G2 1040lm 940 Frosted 11,5W 24Vdc GR 825 mm

Art.no: 102602-01-1

*Lighting Solutions*

Riva G2 1040lm 940 Frosted 11,5W 24Vdc GR 825 mm



The Riva LED Bar is a very slim LED linear light fixture concept designed for use in applications needing narrow width. It is ideal for use on the front side of display shelves in store furniture. The design is focused on high durability / long life time and easy mounting. Max 5 m Riva in line.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	24VDC
Lightsource Max. Power (W) if Socket	11.5

TECHNICAL DATA	
IK (system)	IK08
IP (system)	IP44
Outdoor	No
Operating temperature (°C)	-20 - 40

**PRODUCT DATA SHEET**

Riva G2 1040lm 940 Frosted 11,5W 24Vdc GR 825 mm

Art.no: 102602-01-1

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	90
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	4000
Color Code	940
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Frosted
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
UGR (<=)	26
Manufacturer (light source)	Runlite
Forward Current LED (min-max) (mA)	150 - null
Forward Voltage LED (max tp=25) (V)	3.4
Driftspenning LED (min tp=65) (V)	3.0

DRIVER	
Flicker-free	Yes

DIMENSIONS	
Length (product) (mm)	825.0
Width (product) (mm)	20.0
Height (product) (mm)	14.0
Weight (product) (kg)	0.182

MATERIALS AND SURFACES	
Color	Silver
Corrosion Class	C3
Housing Material	Aluminium 6063
Housing Material %	77.0
Diffuser Material	Polycarbonate
Diffuser Material%	11.0
Recycled Plastic %	93.0
Recycled Aluminium %	95.0
Material 2%	8.5

**PRODUCT DATA SHEET**

Riva G2 1040lm 940 Frosted 11,5W 24Vdc GR 825 mm

Art.no: 102602-01-1

*Lighting Solutions***MATERIALS AND SURFACES**

Material 3%	0.12
Material 4%	2.88
Material 5%	0.5

INSTALLATION AND CONNECTION

Areas of use	Generally, Hotel, Kitchen, Residence
Mounting	Surface, Wall, Ceiling
Connection (system)	Riva 2-pin Connector

ENERGY AND CERTIFICATIONS

Energy Class EPREL	F
CE mark	Yes
Energy Efficiency Class	A++