FAMILY PRODUCT SHEET
Cylinder 60 G2
Art.no: Cylinder-60-G2

Cylinder 60 G2

Cylinder 60 G2 is an elegant and modern spotlight, designed to deliver high light output and exceptional color rendering in various environments. With a diameter of 60mm and length of 130mm, this spotlight is both discreet and efficient. Available with beam angles of 15°, 24°, or 36° and color temperatures of 2700K, 3000K, or Dim 2 Warm (3000-1800K). CRI90 ensures excellent color rendering. Equipped with phase-cut dimming. Made of powder-coated aluminum, Cylinder 60 G2 is ideal for use in bedrooms, cafes, cabins, hotels, kitchens, and homes. The built-in driver in the sleek fixture housing provides a clean and modern appearance, while the spotlight can be tilted up to 90° and rotated 350° around its own axis for optimal adjustability. This makes Cylinder 60 perfect for both private and commercial environments.

VARIANTS

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Connection	Color
102250-36-2-p	14W	1400 lm	2700K	36	Clear	90	Phase-Cut	Skinne 1-fase	Black
102250-36-3-p	14W	1400 lm	2700K	36	Clear	90	Phase-Cut	Skinne 1-fase	White
102251-36-2-p	14W	1400 lm	3000K	36	Clear	90	Phase-Cut	Skinne 1-fase	Black
102251-36-3-p	14W	1400 lm	3000K	36	Clear	90	Phase-Cut	Skinne 1-fase	White
102260-36-3-p	14W	1400 lm	2700K	36	Clear	90	Phase-Cut	Skinne 3-fase	White
102261-36-2-p	14W	1400 lm	3000K	36	Clear	90	Phase-Cut	Skinne 3-fase	Black
102261-36-3-p	14W	1400 lm	3000K	36	Clear	90	Phase-Cut	Skinne 3-fase	White

FAMILY PRODUCT SHEET
Cylinder 60 G2
Art.no: Cylinder-60-G2

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Connection	Color
102260-36-2-p	14W	1400 lm	2700K	36	Clear	90	Phase-Cut	Skinne 3-fase	Black
102261-36-3-ddd	14W	1400 lm	3000K	36	Clear	90	DALI2	Skinne 3-fase	White
102261-36-2-ddd	14W	1400 lm	3000K	36	Clear	90	DALI2	Skinne 3-fase	Black
102251-D2W-36-3-p	14W	800 lm	1800-3000K TWK	36	Clear	95	Phase-Cut	Skinne 1-fase	White
102251-D2W-36-2-p	14W	800 lm	1800-3000K TWK	36	Clear	95	Phase-Cut	Skinne 1-fase	Black
102261-D2W-36-2-p	14W	800 lm	1800-3000K TWK	36	Clear	95	Phase-Cut	Skinne 3-fase	Black
102261-D2W-36-3-p	14W	800 lm	1800-3000K TWK	36	Clear	95	Phase-Cut	Skinne 3-fase	White
102260-36-2-ddd	14W	1400 lm	2700K	36	Clear	90	DALI2	Skinne 3-fase	Black
102262-36-3-ddd	14W	1400 lm	4000K		Clear	90			