FAMILY PRODUCT SHEET
Montana M
Art.no: Montana-M



Montana M

230V 50Hz | IP66 | IK08

Montana feature an innovative, tool-free system that allows for easy replacement of the electrical compartment directly on-site. This ensures fast and efficient maintenance while significantly reducing labor costs and downtime. The sleek and aerodynamic design minimizes wind resistance, enhances reliability, and optimizes heat dissipation, resulting in an extended lifespan. Built to withstand challenging conditions such as Nordic roads and high-altitude environments, Montana deliver dependable performance even in extreme settings.

VARIANTS

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Connection	Color
103030-50-BV-1	50W	7000 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103031-50-BV-1	50W	7500 lm	3000K/4000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103032-50-BV-1	50W	7000 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103033-50-BV-1	50W	7000 lm	3000K/ 2200KK	143°*65°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103030-50-GS-1	50W	7000 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103031-50-GS-1	50W	7500 lm	3000K/4000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103032-50-GS-1	50W	7000 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103033-50-GS-1	50W	7000 lm	3000K/ 2200KK	156°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Connection	Color
103030-50-D-1	50W	7000 lm	3000K	146°*52°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103031-50-D-1	50W	7500 lm	3000K/4000K	146°*52°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103032-50-D-1	50W	7000 lm	3000K	146°*52°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103033-50-D-1	50W	7000 lm	3000K/ 2200KK	146°*52°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103030-60-BV-1	60W	8400 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103031-60-BV-1	60W	9000 lm	3000K/4000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103032-60-BV-1	60W	8400 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103033-60-BV-1	60W	8400 lm	3000K/ 2200KK	143°*65°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103030-60-GS-1	60W	8400 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103031-60-GS-1	60W	9000 lm	3000K/4000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103032-60-GS-1	60W	8400 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103033-60-GS-1	60W	8400 lm	3000K/ 2200KK	156°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103040-90-BV-1	90W	12600 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 10m	Grey
103041-90-BV-1	90W	13500 lm	3000K/4000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 10m	Grey
103042-90-BV-1	90W	12600 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 10m	Grey
103043-90-BV-1	90W	12600 lm	3000K/ 2200KK	143°*65°	PMMA	70	DALI2, D4i	Kabel 10m	Grey
103040-90-GS-1	90W	12600 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 10m	Grey
103041-90-GS-1	90W	13500 lm	3000K/4000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 10m	Grey
103042-90-GS-1	90W	12600 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 10m	Grey
103043-90-GS-1	90W	12600 lm	3000K/ 2200KK	156°*54°	PMMA	70	DALI2, D4i	Kabel 10m	Grey
103040-90-IBV-1	90W	12600 lm	3000K	47.7°*83.2°°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103041-90-IBV-1	90W	13500 lm	3000K/4000K	47.7°*83.2°°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103042-90-IBV-1	90W	12600 lm	3000K	47.7°*83.2°°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103043-90-IBV-1	90W	12600 lm	3000K/ 2200KK	47.7°*83.2°°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103040-90-IBH-1	90W	12600 lm	3000K	41.9°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103041-90-IBH-1	90W	13500 lm	3000K/4000K	41.9°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103042-90-IBH-1	90W	12600 lm	3000K	41.9°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103043-90-IBH-1	90W	12600 lm	3000K/ 2200KK	41.9°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103032-60-BV-1-ddd	60W	8400 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 8m 4x1,5mm2 åpen ende	Grey
103042-90-BV-1-ddd	90W	12600 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 10m 4x1,5mm2 åpen ende	Grey