FAMILY PRODUCT SHEET
Montana S
Art.no: Montana-S



Montana S

Montana feature an innovative, tool-free system that allows for easy replacement of the electrical compartment directly on-site. This ensures fast and efficient maintenance while significantly reducing labor costs and downtime. The sleek and aerodynamic design minimizes wind resistance, enhances reliability, and optimizes heat dissipation, resulting in an extended lifespan. Built to withstand challenging conditions such as Nordic roads and high-altitude environments, Montana deliver dependable performance even in extreme settings.

VARIANTS

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Connection	Color
103020-20-BV-1	20W	2800 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103021-20-BV-1	20W	3000 lm	3000K/4000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103022-20-BV-1	20W	2800 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103023-20-BV-1	20W	2800 lm	3000K/ 2200KK	143°*65°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103020-20-GS-1	20W	2800 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103021-20-GS-1	20W	3000 lm	3000K/4000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103022-20-GS-1	20W	2800 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103023-20-GS-1	20W	2800 lm	3000K/ 2200KK	156°*54°	PMMA	70	DALI2, D4i	Kabel 6m	Grey

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Connection	Color
103020-30-BV-1	30W	4200 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103021-30-BV-1	30W	4500 lm	3000K/4000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103022-30-BV-1	30W	4200 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103023-30-BV-1	30W	4200 lm	3000K/ 2200KK	143°*65°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103020-30-GS-1	30W	4200 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103021-30-GS-1	30W	4500 lm	3000K/4000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103022-30-GS-1	30W	4200 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103023-30-GS-1	30W	4200 lm	3000K/ 2200KK	156°*54°	PMMA	70	DALI2, D4i	Kabel 6m	Grey
103030-40-BV-1	40W	5600 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103031-40-BV-1	40W	6000 lm	3000K/4000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103032-40-BV-1	40W	5600 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103033-40-BV-1	40W	5600 lm	3000K/ 2200KK	143°*65°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103030-40-GS-1	40W	5600 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103031-40-GS-1	40W	6000 lm	3000K/4000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103032-40-GS-1	40W	5600 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103033-40-GS-1	40W	5600 lm	3000K/ 2200KK	156°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103022-30-BV-1-ddd	30W	4200 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 6m 4x1,5mm2 åpen ende	Grey