







Milo Wallwasher 4000lm 930 40/35/30W WH 3-circ Phasecut

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-10 - 35

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	100

PHOTOMETRIC DATA	
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	3000
Color Code	930
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Lens
Lifetime (h) IEC 62717	L80B10: 100 000
MacAdam (SDCM)	3
Manufacturer (light source)	Smalite
Forwrard Voltage LED (max tp=25) (V)	32.0
Driftspenning LED (min tp=65) (V)	38.0

DRIVER	
Manufacturer (driver)	Kinglumi
Protection Class (driver)	2
Flicker metric (Pst LM) <	0.8
Stroboscopic effect metric (SVM) <	0.3
Dimming (driver)	Phase-Cut
Dimming Minimum Level (%)	1.0
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Flicker-free	Yes
Constant current or voltage (CC or CV)	CC
Surge Protection	L-N = 1KV
Current Ripple (%)	12.0
Inrush current time (µs)	115.0
Inrush current Imax (A)	25.0

DIMENSIONS	
Length (product) (mm)	212.0
Width (product) (mm)	52.0
Heigth (product) (mm)	162.0

MATERIALS AND SURFACES	
Color	White

MATERIALS AND SURFACES	
RAL Code	RAL9003

INSTALLATION AND CONNECTION	
Areas of use	Hotel, Museum, Restaurant, Shop, Showroom
Mounting	Track
Connection (system)	Track 3-Circuit

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	F
CE mark	Yes

LIGHT DISTRIBUTION

