

# Cold 5 Mini 950lm 927 50° 5x2,1W BK Phasecut

CE | 230V 50Hz | IP20 | IK00

F (A ↑ G)

| SPECIFICATIONS | |
|---|---|
| Type of Dimming (system) | Phase-Cut |
| IK | IK00 |
| Lumen Out (system) (lm) | 620 |
| Color Code | 927 |
| Lightsource Type | LED (built in) |
| Lifetime (h) | L80B10: 100 000 |
| Forwrard Voltage LED (max tp=25) (V) | 16.0 |
| Forward Voltage LED (min tp=65) (V) | 14.0 |
| Protection Class (driver) | 2 |
| Dimming (driver) | Phase-Cut |
| Constant current or voltage (CC or CV) | CC |
| CC (driver) [mA] | 700 |
| CC (forward voltage driver) (V) | 18.0 |

| SPECIFICATIONS | |
|---|---|
| Inrush current time (µs) | 300.0 |
| Inrush current Imax (A) | 5.0 |
| Length (product) (mm) | 105.0 |
| Width (product) (mm) | 33.0 |
| Heigth (product) (mm) | 50.0 |
| Weight (product) (kg) | 0.26 |
| Color | Black |
| RAL Code | RAL9003 |
| Mounting | Recessed, Ceiling |
| Connection (system) | Terminal |

## LIGHT DISTRIBUTION

