
FDV DOCUMENTATION
Acrux G2 Adj 750lm 930 8W 36° WH Phasecut IP54
Art.no: 2307-36-3





Acrux G2 Adj 750lm 930 8W 36° WH Phasecut IP54

230V 50Hz | IP54 | IK03

F A↑G

SPECIFICATIONS	
Type of Dimming (system)	Phase-Cut
IK	IK03
Operating temperature (°C)	45
Color Code	930
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
Forwrard Voltage LED (max tp=25) (V)	40.0
Forward Voltage LED (min tp=65) (V)	30.0
Protection Class (driver)	2
Dimming (driver)	Phase-Cut
Constant current or voltage (CC or CV)	CC

SPECIFICATIONS	
CC (driver) [mA]	180
CC (forward voltage driver) (V)	40.0
Inrush current time (µs)	312.0
Inrush current Imax (A)	2.64
Heigth (product) (mm)	40.0
Weight (product) (kg)	0.34
Diameter (product) (mm)	95.0
Color	White
RAL Code	RAL9016
Mounting	Recessed, Ceiling
Connection (system)	QuickConnect