



T-Line 7500lm 935 90° 50(45-60W) 1500mm 3-Circuit WH

230V 50Hz | IP20 | IK02

F A G

T-Line Louvre is the latest addition to our T-Line family, designed with a focus on maximum light output and minimal glare. This revolutionary lighting solution provides strong, clear illumination that is comfortable for the eyes, making it ideal for both professional and residential environments.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	DIPswitch
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK02
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-25 - 60

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	166
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	3500
Color Code	935
Lightsource Type	LED (built in)
Lens (Diffuser)	Lens
Lifetime (h) IEC 62717	L80B10: 100 000
MacAdam (SDCM)	3
UGR (<=)	19

DRIVER	
Manufacturer (driver)	Coreshine
Protection Class (driver)	1
Dimming (driver)	None
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Flicker-free	Yes
Constant current or voltage (CC or CV)	CC
Current setting (driver)	DIP-switch
Surge Protection	L-N = 1KV
Max load pr circuit - B10	24
Max load pr circuit - B16	30
Max load pr circuit - C10	24
Max load pr circuit - C16	38
Max load pr circuit - C25	60
Max load pr circuit - C32	76
Leakage current (mA)	0.95
Inrush current time (µs)	136.0
Inrush current Imax (A)	20.0

DIMENSIONS	
Length (product) (mm)	1495.0
Width (product) (mm)	60.0
Heigth (product) (mm)	11.0
Weight (product) (kg)	1.32

INSTALLATION AND CONNECTION	
Areas of use	Cafe, Generally, Industrial, Museum, Office, Open access areas, Shop, Showroom
Mounting	Track
Connection (system)	Track 3-Circuit

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	F
CE mark	Yes

LIGHT DISTRIBUTION

