FAMILIEDATABLAD
Columba
Art.no: Columba-Base



Columba

230V 50Hz | IP65 | IK08

A++

Surface mounted or suspended LED luminaire for use in industry, warehouse, hall and sports arena. Choose between various editions with different lumen output, optics and DALI2 driver.

VARIANTER

Art.no.	Effekt	Lumen ut	Fargetemp.	Strålevinkel	Linse	CRI (>)	Dimming	Lengde	Farge
5711-03-3-ddd	59W	10472 lm	4000K	120°x120°		80		935.0 mm	Hvit
5711-04-3-ddd	59W	9921 lm	4000K	90°x90°		80		935.0 mm	Hvit
5712-03-3-ddd	86W	15627 lm	4000K	120°x120°		80		1190.0 mm	Hvit
5712-04-3-ddd	86W	14805 lm	4000K	90°x90°		80		1190.0 mm	Hvit
5713-03-3-ddd	115W	20837 lm	4000K	120°x120°		80		1440.0 mm	Hvit
5713-04-3-ddd	115W	19740 lm	4000K	90°x90°		80		1444.0 mm	Hvit
5714-03-3-ddd	172W	31094 lm	4000K	120°x120°		80		1953.0 mm	Hvit
5714-04-3-ddd	172W	29457 lm	4000K	90°x90°		80		1953.0 mm	Hvit